



Instruction Manual

Cooker Hood

คู่มือการใช้งานเครื่องดูดควัน

HS-BKT62C-60

Content

- 1..... ข้อควรระวังเพื่อความปลอดภัย
- 2..... การติดตั้ง
- 3..... การเริ่มการใช้งานเครื่องดูดควัน
- 4..... การแก้ไขเบื้องต้น
- 5..... การดูแลรักษาและทำความสะอาด
- 6..... การรักษาสิ่งแวดล้อม

ข้อควรระวังเพื่อความปลอดภัย



ข้อมูลทั่วไป

- a) โปรดอ่านข้อมูลที่สำคัญ ดังต่อไปนี้ เกี่ยวกับความปลอดภัย ในการติดตั้ง และการบำรุงรักษา
- B) เครื่องดูดควันนี้ที่ได้รับการออกแบบมาให้สามารถใช้งานได้สองวิธี คือแบบหมุนเวียน หรือแบบดูดอากาศออกด้านนอก

ข้อควรระวังเพื่อความปลอดภัย

- a) แรงดันลม ในสภาพแวดล้อมในห้อง ต้องไม่เกิน 4 Pa ($4 * 10^{-5}$ บาร์)
- B) ห้องจำเป็นต้องมีการระบายอากาศที่เพียงพอเพื่อการทำงานอย่างปลอดภัยของ เครื่องดูดควัน
- C) ปฏิบัติตามกฎหมายท้องถิ่น ที่ใช้บังคับ สำหรับการระบายอากาศภายนอก
- D) เต้าเสียบปลั๊กไฟ เครื่องดูดควันควรใช้กับเครื่องดูดควันนี้เท่านั้น
- E) เครื่องดูดควันต้องได้รับการทำความสะอาดสม่ำเสมอเพื่อบังกันการติดไฟจากคราบน้ำมันบนผิวเครื่องดูดควัน
- F) ห้ามปล่อยไฟเบลวไฟติดต่อกับเครื่องดูดควัน ขันตรายเครื่องดูดควันอาจเกิดเพลิงไฟได้ - บริษัทจะไม่รับผิดชอบถึงความเสียหายนี้



คำเตือน

ในบางกรณี เครื่องใช้ไฟฟ้าอาจจะเป็นอันตรายได้เมื่อ

- A) ไม่ตรวจสอบสถานะของฟิวเตอร์ที่กรองอุดมเนียมเครื่องดูดควัน ในขณะที่เครื่องทำงาน ห้ามไม่ให้มีคราบน้ำมันสะสม ควรทำความสะอาดฟิวเตอร์ที่กรองอุดมเนียมสม่ำเสมอ
- B) อย่าสัมผัส หลอดไฟหลังการใช้งานเครื่องใช้ไฟฟ้า
- C) อย่าก่อเดลักเครื่องด้วยมือเปียก และ อย่าบิดหรือทำให้สายไฟบิดเบี้ยวผิดรูป
- D) ห้ามทำอาหารโดยใช้เบลวไฟ หรือ ทำ barbecue
- E) หลีกเลี่ยงการทำอาหารที่ทำให้เกิดเบลวไฟเนื่องจากอาจก่อความเสียหายกับตัวกรอง และ อาจเกิดอันตรายจากไฟไหม้
- F) ตรวจสอบอาหารบ่อยครั้ง เมื่อมีการทดสอบอาหาร เพื่อหลีกเลี่ยงอันตรายจากไฟไหม้
- G) ถอน ปลั๊กไฟฟ้า ก่อนที่จะทำการบำรุงรักษาได้
- H) เด็กเล็กต้องอยู่ภายใต้การกำกับดูแลของผู้ใหญ่เมื่อใช้เครื่องดูดควัน




การติดตั้ง

การยึดปีกผีเสื้อ V-FLAP

หากเครื่องดูดควันไม่มีปีกผีเสื้อที่ประกอบแล้วขึ้นนี้ คุณควรประกอบปีกผีเสื้อเข้าด้วยกัน


ในการยึด ผีเสื้อ V-FLAP คุณควร

- ยึดปีกตำแหน่งที่ 2 ตัวเข้ากับตัว ตำแหน่งที่ 6
- เข็มตำแหน่งที่ 3 ควรตั้งตรงขึ้น
- แกน หรือ ศูนย์กลาง ตำแหน่งที่ 4 ควรต่อเข้ากับชุดตำแหน่งที่ 5 บน
- ทำซ้ำกับอีกข้าง




การติดตั้งแบบต่อท่อออกด้านนอก

1. เครื่องดูดควันควรมีระยะห่างจากเตา 65-75cm (20-30 นิ้ว) ตามภาพที่ 1




Pic 1


2. กำหนดตำแหน่งของรู ขนาด $4\Phi 8\text{mm}$ ในการติดตั้งเครื่องดูดควัน
3. ติดตั้ง ตัวแขวน L ด้านบนเครื่องด้วยสกรู 2 ตัว (4 mm. x 10 mm.) ตามภาพ



4. เครื่องดูดควันต้องยึดติดกับผนังและตัวแขวน ด้วยสกรู 4 ตัว (4 mm. x 30 mm.) โดยให้ยึดเครื่องดูดควันกับตัวแขวนผนังด้วยสกรู 2 ตัว (4 mm. x 30 mm.) จากนั้นยึดเครื่องดูดควันเข้ากับผนังด้วยสกรู 2 ตัว (4 mm. x 30 mm.) ตามรูปด้านล่าง




5. ติดตั้งข้อต่อปีกผีเสื้อเข้ากับเครื่องดูดควัน จากนั้นต่อท่ออยู่เข้ากับข้อต่อ และ เดินท่อออกนอกตัวบ้าน ตามภาพ




การติดตั้งแบบติดเข้าตู้เฟอร์นิเจอร์

1. ติดตั้งข้อต่อปีกผีเสื้อเข้ากับเครื่องดูดควันด้วย 2 ตัว (ST4x8) จากนั้นต่อท่ออยู่เข้ากับข้อต่อ และ เดินท่อออกนอกตัวบ้าน ตามภาพ



2. เจาะรู 6 รู ขนาด 6mm บนตู้ และติดตั้งเครื่องเข้ากับตู้ด้วยสกรู 6 ตัว (4x35mm) และหวานชนิดแบน ตามภาพ



หากมีช่องว่างระหว่างผนังกับเครื่องและเครื่องดูดควัน คุณอาจติดตั้ง ตัวแขวนตัว L ให้เครื่องดูดควันด้วยสกรู (3 x 12mm)

ข้อควรจำสำหรับการต่อท่อออกด้านนอก

- ควรให้ท่อสันและตรงที่สุด
- อย่าลดขนาดท่อหรือหักให้ท่อพังงอ
- เมื่อใช้ท่อย่นให้ดึงขยายห่อย่นจนดึงเพื่อลดการเสียประสิทธิภาพในการส่งแรงลม
- หากไม่สามารถขันแน่นข้างตันอาจทำให้ประสิทธิภาพการทำงานลดลงและเสียงของเครื่องดูดควันดังขึ้น
- ช่างผู้ชำนาญการควรเป็นผู้ทำการติดตั้งเท่านั้น
- อย่าต่อท่อระหว่างอากาศเข้ากับระบบระบายอากาศที่มีอยู่แล้ว ซึ่งอาจเป็นระบบระบายอากาศของเครื่องใช้ไฟฟ้าชนิดอื่น เช่น ท่อแก๊ส ท่อระบายน้ำร้อน
- หากจำเป็นต้อง งอ ห่อย่น ไม่ควรงอห่อมากกว่า **120°** คุณควร วางห่อแนวนอนหรือห่อควรส่งขึ้นจากจุดปล่อยลมและส่งออกนอกภายนอก
- หลักการติดตั้งควรดูให้แน่ใจว่าเครื่องดูดควันตั้งตรง เพื่อป้องกันการสะสมของคราบน้ำมัน
- ควรเลือกใช้ท่อย่นที่เป็นไปตามมาตรฐานการท่อไฟ




ข้อควรระวัง

- เพื่อความปลอดภัย ให้เข็นอุตสาหกรรมขนาดเดียวกับที่ระบุไว้ตามคู่มือเท่านั้น
- อันตราย! หากไม่ได้ทำการยึดหรือต่อเครื่องดูดควันตามที่ระบุไว้ในคู่มือเล่มนี้ อาจก่อให้เกิดไฟฟ้าช็อกได้

การเริ่มการใช้งานเครื่องดูดควัน

สวิตซ์แบบปุ่มกด



- สามารถใช้งานได้โดยการเสียบสายไฟเครื่องเข้าเต้าเสียบไฟ
- กดปุ่ม ① ไปที่ เพื่อให้ไฟส่องสว่างทำงาน กดไปที่ “0” เพื่อปิดไฟ
- กดปุ่ม ② ไปที่ ‘.’ และ ‘||’ มอเตอร์จะทำงานด้วยความแรงระดับเบาที่สุด และ ด้วยความแรงที่สุด กดไปที่ “0” เพื่อให้มอเตอร์หยุดทำงาน
- เครื่องจะทำงานเมื่อมีการดึงແงด้านหน้า และเครื่องจะหยุดทำงานเมื่อผลักແงด้านหน้ากลับเข้าตำแหน่ง

การแก้ปัญหาเบื้องต้น

ปัญหา	สาเหตุ	แนวทางแก้ไข
ไฟเครื่องติดแต่ไม่ต่อเครื่อง	สวิทช์มอเตอร์ปิดอยู่	กดเลือกระดับความแรงมอเตอร์
	ไฟสวิทช์เลือกระดับความแรงมอเตอร์เสีย	ติดต่อผู้จำหน่าย
	มอเตอร์เสีย	ติดต่อผู้จำหน่าย
ไฟเครื่องไม่ติดและมอเตอร์ไม่ทำงาน	พิว์สขาด	เปลี่ยนพิว์ส
	สายไฟหลวมหรือไม่ได้เสียบเข้ากับเต้าเสียบ	เสียบสายไฟเข้ากับเต้าเสียบใหม่
พบคราบน้ำมันรั่ว	วาล์วหรือท่อส่งถูกติดตั้งไม่ดี	นำท่อออกและติดตั้งใหม่ และเชื่อมกับข้อต่อต่างๆให้ถูกต้อง
	มีรูรั่วจากข้อต่อตัว U	ถอดข้อต่อตัว U และติดตั้งใหม่
ไฟไม่ทำงาน	ไฟเสีย	เปลี่ยนหลอดไฟใหม่
กำลังแรงดูดไม่แรง	ระยะทางท่อส่งอากาศกับช่องระบายน้ำอาจยาวเกินไป	ต่อท่อใหม่
เครื่องดูดควันเสียง	น็อตยึดหรือตัวยึดไม่แน่น	ยึดน็อตให้แน่น



ข้อควรระวัง

- เพื่อความปลอดภัยการซ่อมบำรุงเกี่ยวกับระบบไฟฟ้าควรทำการตามกฎ ข้อบังคับ ของห้องถิน ควรติดต่อ ศูนย์ซ่อมก่อนการซ่อมบำรุง โปรดดึงปลั๊กออกจากทุกครั้งก่อนเปิดด้านในเครื่อง


การดูแลรักษาและทำความสะอาด

ข้อควรระวัง:

- โปรดดึงปลั๊กเครื่องออกจากเต้าเสียบก่อนการบำรุงรักษาหรือทำความสะอาดเครื่องทุกครั้ง
- พื้นผิวเครื่องดูดควันง่ายต่อการโดนขีดข่วน และการกัดกร่อน โปรดปฏิบัติตามข้อแนะนำเพื่อบังกันความเสียหายที่อาจเกิดขึ้น

ทั่วไป:

- การทำความสะอาดและดูแลรักษาควรทำเมื่อเครื่องดูดควันเย็นลงแล้ว



- หลีกเลี่ยงการใช้ผลิตภัณฑ์ที่เป็นกรดหรือด่าง (น้ำมันน้ำ น้ำส้มสายชู etc)

สเตนเลสสตีล

ควรทำความสะอาดสเตนเลสสตีล (ทุกอย่าง) เพื่อให้เครื่องดูดควันมีอายุการใช้งานที่ยืนยาว ทำความสะอาดด้วยผ้าแห้ง สามารถใช้น้ำยาทำความสะอาดสำหรับสเตนเลสได้

ข้อควรจำ

ให้เช็ดพื้นผิวสเตนเลสตามลาย เพื่อบังกันไม่ให้เกิดรอย
พื้นผิวแห้งคงความ

ควรทำความสะอาดแห้งคงความด้วยผ้าห่มมาตรฐานน้ำสูตร โปรดดูให้มั่นใจว่าผ้าที่ใช้สะอาดและบีบไม้ออกอย่างดีแล้ว ให้ใช้ผ้าแห้งเพื่อเช็ดทำความสะอาดความชื้น หรือ ครบน้ำที่ติดอยู่บนพื้นผิวทุกครั้ง


สิ่งสำคัญ:

โปรดใช้น้ำยาที่ไม่มีฤทธิ์กัดกร่อน ให้ใช้น้ำยาอ่อนๆ เช่นน้ำยาทำความสะอาดภายในบ้านอาจทำให้พื้นผิวสเตนเลสเป็นคราบ เป็นรอย หรือทำให้โลหะซึ่งอาจไม่รับผิดชอบถึงความเสียหายจากการใช้น้ำยาผิดประเภทนี้

ฟิวเตอร์กรองน้ำมัน

ฟิวเตอร์สามารถทำความสะอาดโดยการเชื่อมน้ำผึ้งสมน้ำยาล้างงานประมาณ 3 นาทีและขัดออกเบาๆ ด้วยแปรงอ่อนนุ่ม
อย่าใช้แรงในการขัด เนื่องจากฟิวเตอร์อาจถูกทำลายได้ (นำมาตากให้แห้งด้านนอก)

ฟิวเตอร์ควรนำมาทำความสะอาดแยกกับงานชามและช้อนส้อม หากนำเข้าเครื่องล้างจาน ไม่ควรใส่น้ำยาลินส์เอด



การใส่ฟิวเตอร์กรองน้ำมัน

ใส่ฟิวเตอร์ตามขั้นตอนดังนี้

- ให้วางฟิวเตอร์ให้ตรงกับช่องด้านล่างเครื่องดูดควัน
- กดปุ่มตัวล็อกฟิวเตอร์
- ปลดปุ่มตัวล็อกฟิวเตอร์
- ทำความสะอาดช่องสำหรับการเปลี่ยนฟิวเตอร์


การรับอนฟิวเตอร์ (อุปกรณ์เสริม)

การรับอนฟิวเตอร์จะนำมาใช้เพื่อดูดกลิ่น ควรเปลี่ยนการรับอนทุกๆ 3 หรือ 6 เดือนขึ้นอยู่กับความมากน้อยในการทำอาหาร
ควรใส่ค่ารับอนฟิวเตอร์ตามข้อแนะนำดังนี้

1. ใส่หมุดของตัวกรองการรับอนเข้าไปในรูสีเหลี่ยมของพัดลมมอเตอร์ (ตามลูกศร A ที่แสดงด้านล่าง)
2. ตั้นอีกด้านของตัวกรองการรับอนเข้าหากพัดลมมอเตอร์ (ตามลูกศร B ที่แสดง) จากนั้นกดตัวกรองเข้าไปในพัดลม

มอเตอร์

3. หากคุณต้องการถอดตัวกรองออก ให้กดตัวยึดตัวกรองแล้วถอดออกโดยหมุนทวนเข็มนาฬิกา



ข้อควรระวัง


- โปรดดูให้มั่นใจว่าไฟเตอร์ล็อกกับตัวยึดตีเหลว ไม่เข็นนั่นไฟเตอร์อาจหลุดออกจากตำแหน่งและสร้างความเสียหายกับเครื่องได้
- แรงดูดเครื่องจะลดลงเมื่อใส่คาร์บอนไฟเตอร์



การเปลี่ยนหลอดไฟ

สำคัญ	<ul style="list-style-type: none">หลอดไฟควรได้รับการเปลี่ยนโดยผู้ชำนาญ หรือผู้ที่ได้รับการแต่งตั้งจากผู้จำหน่ายเท่านั้นโปรดปิดเครื่องทุกครั้งก่อนการซ่อม หรือ ทำความสะอาดเครื่อง ดูให้มั่นใจว่าเครื่องนั้นเย็นลงแล้วก่อนสัมผัสในเครื่องควรใส่ถุงมือหรือใช้ผ้าเมื่อสัมผัสในเครื่องหลอดไฟ เพื่อยืดอายุหลอดไฟ

การเปลี่ยนหลอดไฟ LED

- ปิดเครื่องและดึงปลั๊กออกก่อนทุกครั้งที่ต้องการเปลี่ยนหลอดไฟ
- รอให้หลอดไฟเย็นลงก่อนทำการเปลี่ยน
- นำตะแกรงกรองน้ำมันออก ตามขั้นตอนที่ 1
- ถอนปลั๊กขั้วของสายเชื่อมต่อออกแล้ว ใช้ไขควงแฉกเพื่อคลายเกลียวสกรูออก 1 ตัว ดูขั้นตอนที่ 2
- สอดไฟเข้าช่องเดียวกับเดิม ตามภาพ ใช้แรงกดลงเล็กน้อยเพื่อให้โครงหลุดออก และเอาหลอดไฟออก เพื่อนำหลอดใหม่เปลี่ยนและขัดน็อตกลับเข้าที่เดิมเมื่อเปลี่ยนเสร็จเรียบร้อยแล้ว
- ถอนแฉกขั้วส่วนไฟ LED: เปิดแผ่นหลอดไฟ (ซึ่งติดอยู่กับเครื่อง) นำกล่องไฟด้านนอกออกด้านบน คลายเกลียวสกรู 2 ตัวแล้วถอดบอร์ด PCB ออกเพื่อเปลี่ยน ดังที่แสดงตั้งแต่ขั้นตอนที่ 3 ถึงขั้นตอนที่ ⑥
- LED โมดูล – DBS-5/65-H-320/45.2
- กำลังสูงสุด: 1x5 W
- กำลังไฟ: AC 110-240V
- ขนาดหลอดไฟ:





การรักษาสิ่งแวดล้อม



เครื่องหมายนี้คือสัญลักษณ์การเลือกใช้การกำจัดและการทิ้งสินค้า ผลิตภัณฑ์นี้ห้ามนำไปทิ้งตามถังขยะทั่วไปในครัวเรือน แต่ต้องได้รับการทำลายอย่างถูกต้องตาม Directive 2012/19/EU จากนั้นจะถูกนำไปรีไซเคิล หรือแยกชิ้นส่วนเพื่อลดผลกระทบต่อสิ่งแวดล้อม ผลิตภัณฑ์นี้มีลักษณะอันตรายต่อสิ่งแวดล้อมและสุขภาพมนุษย์เนื่องมาจากส่วนประกอบของสารเคมีอันตราย โปรดติดต่อรัฐส่วนภูมิภาคของท่านเพื่อสอบถามข้อมูลเพิ่มเติม

ข้อบังคับต่อไปนี้สำคัญต่อการรักษาสิ่งแวดล้อม (เช่น การประหยัดการใช้พลังงานในการทำอาหาร)

SAFETY INSTRUCTION

This manual explains the proper installation and use of your cooker hood, please read it carefully before using even if you are familiar with the product. The manual should be kept in a safe place for future reference.

Never to do:

- Do not try to use the cooker hood without the grease filters or if the filters are excessively greasy!
- Do not install above a cooker with a high level grill.
- Do not leave frying pans unattended during use because overheated fats or oils might catch fire.
- Never leave naked flames under the cooker hood.



- If the cooker hood is damaged, do not attempt to use.
- Do not flambé under the cooker hood.

CAUTION: Accessible parts may become hot when used with cooking appliances.

- The minimum distance between the supporting surface for the cooking vessels on the hob and the lowest part of the cooker hood. (When the cooker hood is located above a gas appliance, this distance shall be at least 65 cm)
- The air must not be discharged into a flue that is used for exhausting fumes from appliances burning gas or other fuels. Range hoods and other cooking fume extractors may adversely affect the safe operation of appliances burning gas or other fuels (including those in other rooms) due to back flow of combustion gases. These gases can potentially result in carbon monoxide poisoning. After installation of a range hood or other cooking fume extractor, the operation of open flued gas appliances should be tested by a competent person to ensure that back flow of combustion gases does not occur.
- A steam cleaner is not to be used.
- NEVER try to extinguish a fire with water, but switch off the appliance and then cover flame e.g. with a lid or a fire blanket
- Important! Always switch off the electricity supply at the mains during installation and maintenance such as light bulb replacement.
- The cooker hood must be installed in accordance with the installation instructions and all measurements followed.
- All installation work must be carried out by a competent person or qualified electrician.
- Please dispose of the packing material carefully. Children are vulnerable to it.
- Pay attention to the sharp edges inside the cooker hood especially during installation and cleaning.
- Make sure the ducting has no bends sharper than 90 degrees as this will reduce the efficiency of the cooker hood.
- **Warning:** Failure to install the screws or fixing device in accordance with these instructions may result in electrical hazards



- **Warning:** Before obtaining access to terminals, all supply circuits must be disconnected.

Always to do:

- **Important!** Always switch off the electricity supply at the mains during installation and maintenance such as light bulb replacement.
- The cooker hood must be installed in accordance with the installation instructions and all measurements followed.
- All installation work must be carried out by a competent person or qualified electrician.
- Please dispose of the packing material carefully. Children are vulnerable to it.
- Pay attention to the sharp edges inside the cooker hood especially during installation and cleaning.
- Make sure the ducting has no bends sharper than 90 degrees as this will reduce the efficiency of the cooker hood.

Warning: Failure to install the screws or fixing device in accordance with these instructions may result in electrical hazards.

- Warning: Before obtaining access to terminals, all supply circuits must be disconnected.

Always to do:

- Always put lids on pots and pans when cooking on a gas cooker.
- When in extraction mode, air in the room is being removed by the cooker hood. Please make sure that proper ventilation measures are being observed. The cooker hood removes odours from room but not steam.
- There shall be adequate ventilation of the room when the cooker hood is used at the same time as appliances burning gas or other fuels.
- Cooker hood is for domestic use only.



- If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.
- If This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.



INSTALLATION


Installation with the outside vent

MOUNTING OF THE V-FLAP

If the cooker hood does not have an assembled V-flap 1, you should mount the half-parts to its body. The images only show an example of how to mount the V-flap, because the outlet may vary according to different models and configurations.


To mount the V-flap 1 you should:

- Mount two half-parts 2 into the body 6
- the pin 3 should be top oriented;
- the axis 4 should be inserted into the holes 5 on the body;
- repeat all the operations for the 2nd half-part



INSTALLATION (Wall Mounting)

1. The cooker hood should be placed at a distance of 65-75cm from the cooking surface for the best effect. See pic 1.




Pic 1

Pic 2


2. Decide the location of the 4φ8mm holes for fixing the cooker hood.
3. Install the L-shaped bracket on the top of the hood with two screws (4mm x 10mm). See pic 2.

4. The cooker hood is wall mounted with 4 screws (4mm x 30mm) and wall plugs. Mount the cooker hood on the wall on the back of the cooker hood with 2 screws (4mm x 30mm) and wall plugs. Then fix the cooker hood on the wall with 2 screws (4mm x 30mm) and wall plugs through the small L-shaped bracket. See pic 3.



Pic 3


5. Install the outlet to the cooker hood. Then fix the expansion pipe on the outlet, and lead it to outdoors. See pic4.



Pic 4


INSTALLATION (Cabinet Mounting)

1. Fix the outlet to the cooker hood with 2pcs screws(ST4*8). Then fix the expansion pipe on the outlet, and lead it to outdoors. See pic5.



Pic 5

2. Drill 6 φ 6mm holes on the cabinet splint. And mount the cooker hood on the cabinet with 6 screws (4x35mm) and flat washers. See pic 6.



Pic 6

If there is gap between the wall and the cooker hood, you may install the L-shaped bracket on the bottom of the hood with two screws (3 x 12mm).

The installation of the L-shaped bracket is optional.

Note: The expansion pipe mentioned in all installation is not included in the product.





WARNING

- For safety reason, please use only the same size of fixing or mounting screws which are recommended in this instruction manual.
- Failure to install the screws or fixing device in accordance with these instructions may result in electrical hazards.

START USING YOUR COOKER HOOD

Rocker switch



1. Insert the power plug into the socket.

2. Push switch ① to  , the lamp will be on; push switch ① to “0”, the lamp will be off.

3. Push the switch ② into “I、II”, the motor will be on “low、high” two speeds, push into “0”, the motor will be off.
4. The power will be connected when pull out the front panel. Conversely, the power will be automatically disconnected.

TROUBLE SHOOTING

Fault	Possible Cause	Solution
Light on, but motor does not work	Fan switch turned off	Select a fan switch position.
	Fan switch failed	Contact service center.
	Motor failed	Contact service center.
Light does not work, motor does not work	House fuses blown	Reset/Replace fuses.
	Mains power cable is loose or disconnected	Refit mains power cable to power outlet. Switch power outlet on.
Oil leakage	One way valve and the outlet are not tightly sealed	Take down the one way valve and seal with sealant.
	Leakage from the connection of chimney and cover	Take chimney down and seal.
Lights not working	Broken or faulty bulbs	Replace bulbs as per this instruction.
Insufficient suction	The distance between the cooker hood and the gas top is too far	Refit the cooker hood to the correct distance.
The Cooker hood inclines	The fixing screw is not tight enough	Tighten the hanging screw and make it horizontal.




CAUTION!

Any electrical repairs to this appliance must conform to your local, state and federal laws. Please contact the service centre if in any doubt before undertaking any of the above. Always disconnect the unit from the power source when opening the unit.

MAINTENANCE AND CLEANING

CAUTION:

- Before maintenance or cleaning is carried out, the cooker hood should be disconnected from the mains power supply. Ensure that the cooker hood is switched off at the wall socket and the plug removed.
- External surfaces are susceptible to scratches and abrasions, so follow the cleaning instructions to ensure the best possible result is achieved without damage.



GENERAL:

- Cleaning and maintenance should be carried out with the appliance cold especially when cleaning. Avoid leaving alkaline or acid substances (lemon juice, vinegar etc.) on the surfaces.

STAINLESS STEEL

The stainless steel must be cleaned regularly (e.g. weekly) to ensure a long life expectancy. Dry with a clean soft cloth. A specialized stainless steel cleaning fluid may be used.

IMPORTANT:

Ensure that wiping is done along with the grain of the stainless steel to prevent any unsightly crisscross scratching patterns from appearing.

CONTROL PANEL SURFACE

The inlay control panel can be cleaned using warm soapy water. Ensure the cloth is clean and well wrung before cleaning. Use a dry soft cloth to remove any excess moisture left after cleaning.

IMPORTANT:

Using neutral detergents and avoid using harsh cleaning chemicals, strong household detergents or products containing abrasives, as this will affect the appearance of the appliance and potentially remove any printing or artwork on the control panel and will void manufacturers warranty.

GREASE MESH FILTERS


The mesh filters can be cleaned by hand. Soak them for about 3 minutes in water with a mild detergent and then brush it gently with a soft brush. Do not apply too much pressure so as to avoid any damage to it. (Leave to dry naturally out of direct sun light)

Filters should be washed separately to crockery and kitchen utensils. It is advisable not to use rinse aid.

INSTALLING GREASE FILTERS

- **To install filters for the following four steps:**

- Angle the filter into the slots at the back of the hood.
- Push the button on the handle of the filter.
- Release the handle once the filter fits into a resting position.
- Repeat to install all filters.



CARBON FILTER

Activated carbon filter can be used to trap odors. Normally the activated carbon filter should be changed every 3 to 6 months according to your cooking habits. The installation procedure of activated carbon filter is as below:

- ✧ Put the pin of the carbon filter into the rectangular hole of the fan(as per the arrow A shown below)
- ✧ Push the other side of the carbon filter toward the fan to make it flat(as per the arrow B shown),and then press filter into fan.
- ✧ If you want to remove the filter, press fastener of filter and remove it by turning anticlockwise.



NOTE:

- Make sure the filter is securely locked. Otherwise, it would loosen and cause danger.
- When activated carbon filter attached, the suction power will be lowered

BULB REPLACEMENT

IMPORTANT



- The bulb must be replaced by the manufacturer, its service agent or similarly qualified persons.
- Always switch off the electricity supply before carrying out any operations on the appliance. When handling bulb, make sure it has completely cooled down before any direct contact with hands
- When handling bulbs hold with a cloth or gloves to ensure perspiration does not come in contact with the bulb as this can reduce the life of the bulb.



Note:

- Before changing the lights, make sure that the appliance is turned off and unplugged.
- Protect against danger when changing lights, such as wearing gloves.

Changing the lights:

- Remove the hood and aluminum filter. See step ①.
- Unplug the terminal of connecting wire and use cross screwdriver to unscrew 1pcs screw. See step ②.
- Disassemble the LED light: open the lamp plate(which is are affixed to the hood), take out the outer case of light upwardly, unscrew 2pcs screws and remove the PCB board for replacement. As shown from step ③ to step ⑥.
- Apply the reverse procedure to install the light strip back.
- ILCOS D code for this lamp is: DBS-5/65-H-320/45.2
 - LED modules –rectangle LED light
 - Max wattage: 1x 5 W
 - Voltage range: AC 110-240V

Dimensions:



ENVIRONMENTAL PROTECTION



This product is marked with the symbol on the selective sorting of waste electronic equipment. This means that this product must not be disposed of with household waste but must be supported by a system of selective collection in accordance with Directive 2012/19/EU. It will then be recycled or dismantled to minimize impacts on the environment, electrical and electronic products are potentially dangerous for the environment and human health due to the presence of hazardous substances. For more information, please contact your local or regional authorities.

NOTE:

The following shows how to reduce total environmental impact (e.g. energy use) of the cooking process).

- (1) Install the cooker hood in a proper place where there is efficient ventilation.
- (2) Clean the cooker hood regularly so as not to block the airway.
- (3) Remember to switch off the cooker hood light after cooking.
- (4) Remember to switch off the cooker hood after cooking.

INFORMATION FOR DISMANTLING

Do not dismantle the appliance in a way which is not shown in the user manual. The appliance could not be dismantled by user. At the end of life, the appliance should not be disposed of with household waste. Check with your Local Authority or retainer for recycling advice.

